


## CUSTOM-MADE


OTHER CLASSES ARE AVAILABLE, SUCH AS H8, H9  
OTHER DIAMETERS ARE AVAILABLE, SUCH AS 19.003mm  
OTHER LENGTHS ARE AVAILABLE, SUCH AS 70mm

## PLAIN PLUG GAGES




4124-12

Type A



Type A

Type B



Type B

- Supplied with Go and No-Go gages together
- Class H7
- Hardness HRC 60±2
- Standard DIN7150-2

Size tolerance of H7 (mm)

Diameter ϕd	Type	Size tolerance of Go gage (µm)	Size tolerance of No-Go gage (µm)	L1	L2	L	S1, S2
≥2, ≤3	A	+0.5 / +2.5	+9 / +11	6.5	4.5	62	—
>3, ≤6	A	+0.75 / +3.25	+10.75 / +13.25	8	6	74	—
>6, ≤10	A	+0.75 / +3.25	+13.75 / +16.25	10	7	87	—
>10, ≤14	A	+1 / +4	+16.5 / +19.5	12	8	99	—
>14, ≤18	A	+1 / +4	+16.5 / +19.5	14	10	114	—
>18, ≤24	A	+1 / +5	+19 / +23	16	12	132	—
>24, ≤30	A	+1 / +5	+19 / +23	18	14	136	—
>30, ≤40	A	+1.5 / +5.5	+23 / +27	20	15	155	—
>40, ≤50	A	+1.5 / +5.5	+23 / +27	25	18	169	—
>50, ≤65	B	+1.5 / +6.5	+27.5 / +32.5	30	18	—	164, 152
>65, ≤80	B	+1.5 / +6.5	+27.5 / +32.5	35	25	—	169, 159
>80, ≤100	B	+2 / +8	+32 / +38	35	25	—	169, 159

Code	Diameter	Type	Code	Diameter	Type	Code	Diameter	Type	Code	Diameter	Type
4124-2	2mm	A	4124-17	17mm	A	4124-32	32mm	A	4124-47	47mm	A
4124-3	3mm	A	4124-18	18mm	A	4124-33	33mm	A	4124-48	48mm	A
4124-4	4mm	A	4124-19	19mm	A	4124-34	34mm	A	4124-49	49mm	A
4124-5	5mm	A	4124-20	20mm	A	4124-35	35mm	A	4124-50	50mm	A
4124-6	6mm	A	4124-21	21mm	A	4124-36	36mm	A	4124-52	52mm	B
4124-7	7mm	A	4124-22	22mm	A	4124-37	37mm	A	4124-55	55mm	B
4124-8	8mm	A	4124-23	23mm	A	4124-38	38mm	A	4124-60	60mm	B
4124-9	9mm	A	4124-24	24mm	A	4124-39	39mm	A	4124-65	65mm	B
4124-10	10mm	A	4124-25	25mm	A	4124-40	40mm	A	4124-70	70mm	B
4124-11	11mm	A	4124-26	26mm	A	4124-41	41mm	A	4124-75	75mm	B
4124-12	12mm	A	4124-27	27mm	A	4124-42	42mm	A	4124-80	80mm	B
4124-13	13mm	A	4124-28	28mm	A	4124-43	43mm	A	4124-85	85mm	B
4124-14	14mm	A	4124-29	29mm	A	4124-44	44mm	A	4124-90	90mm	B
4124-15	15mm	A	4124-30	30mm	A	4124-45	45mm	A	4124-95	95mm	B
4124-16	16mm	A	4124-31	31mm	A	4124-46	46mm	A	4124-100	100mm	B