

## CUSTOM-MADE

OTHER CLASSES ARE AVAILABLE, SUCH AS H8, H9  
OTHER DIAMETERS ARE AVAILABLE, SUCH AS 19.003mm  
OTHER LENGTHS ARE AVAILABLE, SUCH AS 70mm

## PLAIN PLUG GAGES


- Supplied with Go and No-Go gages together
- Class H7
- Hardness HRC 60±2
- Standard DIN7150-2




4124-12

### Size tolerance of H7

Diameter Ød	Size tolerance of Go gage (µm)	Size tolerance of No-Go gage (µm)	L1	L2	L	S1, S2	(mm)
≥2, ≤3	+0.5 / +2.5	+9 / +11	6.5	4.5	62	–	
>3, ≤6	+0.75 / +3.25	+10.75 / +13.25	8	6	74	–	
>6, ≤10	+0.75 / +3.25	+13.75 / +16.25	10	7	87	–	
>10, ≤14	+1 / +4	+16.5 / +19.5	12	8	99	–	
>14, ≤18	+1 / +4	+16.5 / +19.5	14	10	114	–	
>18, ≤24	+1 / +5	+19 / +23	16	12	132	–	
>24, ≤30	+1 / +5	+19 / +23	18	14	136	–	
>30, ≤40	+1.5 / +5.5	+23 / +27	20	15	155	–	
>40, ≤50	+1.5 / +5.5	+23 / +27	25	18	169	–	
>50, ≤65	+1.5 / +6.5	+27.5 / +32.5	30	18	–	164, 152	
>65, ≤80	+1.5 / +6.5	+27.5 / +32.5	35	25	–	169, 159	
>80, ≤100	+2 / +8	+32 / +38	35	25	–	169, 159	




Type A



Type A



Type B



Type B

Code	Diameter (mm)	Type
4124-2	2	A
4124-3	3	A
4124-4	4	A
4124-5	5	A
4124-6	6	A
4124-7	7	A
4124-8	8	A
4124-9	9	A
4124-10	10	A
4124-11	11	A
4124-12	12	A
4124-13	13	A
4124-14	14	A
4124-15	15	A
4124-16	16	A

Code	Diameter (mm)	Type
4124-17	17	A
4124-18	18	A
4124-19	19	A
4124-20	20	A
4124-21	21	A
4124-22	22	A
4124-23	23	A
4124-24	24	A
4124-25	25	A
4124-26	26	A
4124-27	27	A
4124-28	28	A
4124-29	29	A
4124-30	30	A
4124-31	31	A

Code	Diameter (mm)	Type
4124-32	32	A
4124-33	33	A
4124-34	34	A
4124-35	35	A
4124-36	36	A
4124-37	37	A
4124-38	38	A
4124-39	39	A
4124-40	40	A
4124-41	41	A
4124-42	42	A
4124-43	43	A
4124-44	44	A
4124-45	45	A
4124-46	46	A

Code	Diameter (mm)	Type
4124-47	47	A
4124-48	48	A
4124-49	49	A
4124-50	50	A
4124-52	52	B
4124-55	55	B
4124-60	60	B
4124-65	65	B
4124-70	70	B
4124-75	75	B
4124-80	80	B
4124-85	85	B
4124-90	90	B
4124-95	95	B
4124-100	100	B